

# KEL-U-BS cable entry frames with fire penetration seals (EN 45545-3)

for cables with connectors / IP54 / UL Type 12



icotech cable entry frames with fire penetration seals, approved for use in [railway technology](#) (meeting the standards EN 45545-2, EN 45545-3 and EN 1363-1).

Split cable entry system for routing cables with connectors providing an IP54 / UL type 12 rating. Routing, sealing and providing strain relief for cable diameters from 1 to 35 mm. The cable entry system is easy to install. [Cable grommets](#) are placed into compartments and are securely fixed to the frame during assembly.

The KEL-U-BS frame matches exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. The KEL-U-B-BS frame matches exactly the cut-out dimensions of 46 x 46 mm measuring instruments. The single-row version KEL-E-BS is particularly suited for flat connectors. The small frame is ideal for applications with limited space. A flat rubber gasket is included in the shipment.

The intumescent (foaming) IFPS fire penetration seals which are mounted at the backside of the cable entry components consist of expandable graphite and increase their volume by a multiple in case of a fire.

This creates a barrier which prevents a penetration of flames and high heat from one room into another for the longest possible period.

IP54

UL TYPE  
12

UL  
US

HL3  
EN 45545-2

E45  
EI30  
EN 45545-3

EN 61373

ECOLAB  
certified

UV  
ISO 4892-2A

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

## Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	silicone free, intumescent (foaming), halogen free
Mounting options	Screw type mounting

## Advantages & benefits

- Approved for use in railway technology (EN 45545-2, EN 45545-3, EN 1363-1 and EN 61373)
- Only one fire penetration seal per cable entry component required
- High classifications E45 / EI30
- Greatly increased cable density when using double or quadruple grommets
- Fast and easy assembly
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant
- Space-saving shape
- Perfect for routing D-Sub connectors


## Product types & sizes

KEL-U 24|10-BS




Part No.	<b>99300.003</b>
EAN	<b>4251269318436</b>
Package quantity	<b>5</b>
For max. no. of cables	<b>40</b>
Max. cable diameter	<b>17 mm</b>
Length	<b>147 mm</b>
Width	<b>58 mm</b>


Height	<b>17 mm</b>
Mounting height	<b>17 mm</b>
Cut-out size	<b>112 x 36 mm</b>
No. of screw holes	<b>4</b>
Diam. of screw holes	<b>5,8 mm</b>
Screw material	<b>Mild steel, galvanically zinc plated</b>
Suitable for grommets	<b>10 x KT small</b>

**KEL-U 24|10-BS V2A**


Part No.	<b>99300.203</b>	Height	<b>17 mm</b>
EAN	<b>4251269318788</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 × 36 mm</b>
For max. no. of cables	<b>40</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>10 x KT small</b>

**KEL-U 24|7-BS**


Part No.	<b>99300.002</b>	Height	<b>17 mm</b>
EAN	<b>4251269318429</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 × 36 mm</b>
For max. no. of cables	<b>25</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>6 x KT small 1 x KT large</b>

**KEL-U 24|7-BS V2A**


Part No.	<b>99300.202</b>	Height	<b>17 mm</b>
EAN	<b>4251269318771</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 × 36 mm</b>
For max. no. of cables	<b>25</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>6 x KT small 1 x KT large</b>

**KEL-U 24|4-BS**


Part No.	<b>99300.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269318412</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 × 36 mm</b>
For max. no. of cables	<b>10</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>2 x KT small 2 x KT large</b>

**KEL-U 24|4-BS V2A**


Part No.	<b>99300.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269318764</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 × 36 mm</b>
For max. no. of cables	<b>10</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>2 x KT small 2 x KT large</b>

**KEL-U 16|8-BS**


Part No.	<b>99301.003</b>	Height	<b>17 mm</b>
EAN	<b>4251269318498</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 36 mm</b>
For max. no. of cables	<b>32</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>8 x KT small</b>

**KEL-U 16|8-BS V2A**


Part No.	<b>99301.203</b>	Height	<b>17 mm</b>
EAN	<b>4251269318849</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 36 mm</b>
For max. no. of cables	<b>32</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>8 x KT small</b>

**KEL-U 16|5-BS**


Part No.	<b>99301.002</b>	Height	<b>17 mm</b>
EAN	<b>4251269318481</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 36 mm</b>
For max. no. of cables	<b>17</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>4 x KT small 1 x KT large</b>

**KEL-U 16|5-BS V2A**


Part No.	<b>99301.202</b>	Height	<b>17 mm</b>
EAN	<b>4251269318832</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 36 mm</b>
For max. no. of cables	<b>17</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>4 x KT small 1 x KT large</b>

**KEL-U 16|2-BS**


Part No.	<b>99301.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269318474</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 36 mm</b>
For max. no. of cables	<b>2</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>2 x KT large</b>

**KEL-U 16|2-BS V2A**


Part No.	<b>99301.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269318825</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 × 36 mm</b>
For max. no. of cables	<b>2</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>2 x KT large 0 x KT small</b>

**KEL-U 10|6-BS**


Part No.	<b>99306.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269320644</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>65 × 36 mm</b>
For max. no. of cables	<b>24</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>98 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>6 x KT small</b>

**KEL-U 10|6-BS V2A**


Part No.	<b>99306.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269321924</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>65 × 36 mm</b>
For max. no. of cables	<b>24</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>98 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>6 x KT small</b>

**KEL-U 10|3-BS**


Part No.	<b>99306.002</b>	Height	<b>17 mm</b>
EAN	<b>4251269320651</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>65 × 36 mm</b>
For max. no. of cables	<b>9</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>98 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>2 x KT small 1 x KT large</b>

**KEL-U 10|3-BS V2A**


Part No.	<b>99306.202</b>	Height	<b>17 mm</b>
EAN	<b>4251269321931</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>65 × 36 mm</b>
For max. no. of cables	<b>9</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>98 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>2 x KT small 1 x KT large</b>

**KEL-U-B4-BS**


Part No.	<b>99305.002</b>	Height	<b>17 mm</b>
EAN	<b>4251269320613</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>46 × 46 mm</b>
For max. no. of cables	<b>16</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>73 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>4 x KT small</b>

**KEL-U-B4-BS V2A**


Part No.	<b>99305.202</b>	Height	<b>17 mm</b>
EAN	<b>4251269321894</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>46 × 46 mm</b>
For max. no. of cables	<b>16</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>73 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>4 x KT small</b>

**KEL-U-B1-BS**

Part No.	<b>99305.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269320606</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>46 × 46 mm</b>
For max. no. of cables	<b>1</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>73 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>1 x KT large 0 x KT small</b>

**KEL-U-B1-BS V2A**


Part No.	<b>99305.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269321887</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>46 × 46 mm</b>
For max. no. of cables	<b>1</b>	No. of screw holes	<b>4</b>
Max. cable diameter	<b>35 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>73 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>58 mm</b>	Suitable for grommets	<b>1 x KT large 0 x KT small</b>

**KEL-E5-BS**


Part No.	<b>99302.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269318535</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 × 24 mm</b>
For max. no. of cables	<b>20</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>5 x KT small 0 x KT small</b>

**KEL-E5-BS V2A**


Part No.	<b>99302.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269318887</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>112 x 24 mm</b>
For max. no. of cables	<b>20</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>147 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>5 x KT small</b>

**KEL-E4-BS**


Part No.	<b>99309.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269321795</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 24 mm</b>
For max. no. of cables	<b>16</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>4 x KT small</b>

**KEL-E4-BS V2A**


Part No.	<b>99309.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269321818</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>86 x 24 mm</b>
For max. no. of cables	<b>16</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>120 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>4 x KT small</b>

**KEL-E3-BS**


Part No.	<b>99308.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269321757</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>65 x 24 mm</b>
For max. no. of cables	<b>12</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>98 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>3 x KT small</b>

**KEL-E3-BS V2A**

Part No.	<b>99308.201</b>	Height	<b>17 mm</b>
EAN	<b>4251269321771</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>65 x 24 mm</b>
For max. no. of cables	<b>12</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>98 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>3 x KT small</b>

**KEL-E2-BS**

Part No.	<b>99307.001</b>	Height	<b>17 mm</b>
EAN	<b>4251269321719</b>	Mounting height	<b>17 mm</b>
Package quantity	<b>5</b>	Cut-out size	<b>43 x 24 mm</b>
For max. no. of cables	<b>8</b>	No. of screw holes	<b>2</b>
Max. cable diameter	<b>17 mm</b>	Diam. of screw holes	<b>5,8 mm</b>
Length	<b>73 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
Width	<b>39 mm</b>	Suitable for grommets	<b>2 x KT small</b>

**KEL-E2-BS V2A**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Max. cable diameter  
Length  
Width

**99307.201**  
**4251269321733**  
**5**  
**8**  
**17 mm**  
**73 mm**  
**39 mm**

Height  
Mounting height  
Cut-out size  
No. of screw holes  
Diam. of screw holes  
Screw material  
Suitable for grommets

**17 mm**  
**17 mm**  
**43 × 24 mm**  
**2**  
**5,8 mm**  
**Stainless steel (V2A)**  
**2 x KT small**

---

**icotek**<sup>®</sup>  
smart cable management