

KEL | Centrally split cable entry frames

for cables with connectors / IP54 / UL Type 12



IP54

UL TYPE
12

C_{RU}US



RIFA

HL3
EN 45545-2



ECOLAB
certified



RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

The classic KEL is a centrally split cable entry system for routing cables with connectors, providing an IP54 / up to UL Type 12 rating.

The slit [KT grommet](#) matching the cable diameter is placed around the cable and inserted into the cable entry frame. The split cable entry frames KEL match exactly the cut-out dimensions of 10-, 16- and 24-pin standard industrial connectors. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. The size KEL-B matches the cut-out dimensions of 46 x 46 mm measuring instruments.

Based on the frame sizes KEL 16 and KEL 24, there are also extended versions with additional middle frames available. Thus allowing a quick, easy and cost effective routing solution for up to 120 cables or hoses.

For tool-free assembly / disassembly of the cable entry frames the [snap mounting frame KEL-SNAP](#) can be used.

A flat rubber gasket is included in the shipment.

This product is available in different versions: With steel screws or stainless steel screws. It is also possible to integrate threaded bushings. Please ask us about your desired variant.

The version with threaded bushings enables the cable entry frame to be screwed onto the housing from the inside out. This protects against vandalism and tampering with the housing from the outside.

Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, silicone free, anti-corrosive (V2A versions), halogen free, UV-resistant
Mounting options	Screw type mounting, Snap-in with KEL-SNAP
Mounting height	17 mm

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant
- Space-saving shape
- Greatly increased cable density when using double or quadruple grommets


Product types & sizes

KEL 24|10




Part No.	42241
EAN	4251269308277
Package quantity	10
For max. no. of cables	40
Max. cable diameter	17 mm
Length	147 mm
Width	58 mm


Height	17 mm
Mounting height	17 mm
Cut-out size	112 x 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm
Screw material	Mild steel, galvanically zinc plated
Min. cable diam., with connector Suitable for grommets	10 x KT small

KEL 24|10 V2A


Part No.	42241.200	Height	17 mm
EAN	4251269308284	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	40	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	10 x KT small

KEL 24|7


Part No.	42247	Height	17 mm
EAN	4251269308314	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	25	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	6 x KT small 1 x KT large

KEL 24|7 V2A


Part No.	42247.200	Height	17 mm
EAN	4251269308321	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	25	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	6 x KT small 1 x KT large

KEL 24|5


Part No.	42248	Height	17 mm
EAN	4251269308338	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	20	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	5 x KT small

KEL 24|5 V2A


Part No.	42248.200	Height	17 mm
EAN	4251269308345	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	20	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	5 x KT small

KEL 24|4


Part No.	42244	Height	17 mm
EAN	4251269308291	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	10	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT small 2 x KT large

KEL 24|4 V2A


Part No.	42244.200	Height	17 mm
EAN	4251269308307	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	10	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT small 2 x KT large

KEL 24|15-E


Part No.	42209	Height	17 mm
EAN	4251269308017	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	60	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	83 mm	Min. cable diam., with connector	
		Suitable for grommets	15 x KT small

KEL 24|15-E V2A


Part No.	42209.200	Height	17 mm
EAN	4251269308024	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	60	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	83 mm	Min. cable diam., with connector	
		Suitable for grommets	15 x KT small

KEL 24|12-E


Part No.	42208	Height	17 mm
EAN	4251269307997	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	45	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	83 mm	Min. cable diam., with connector	
		Suitable for grommets	11 x KT small 1 x KT large

KEL 24|12-E V2A


Part No.	42208.200	Height	17 mm
EAN	4251269308000	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	45	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	83 mm	Min. cable diam., with connector	11 x KT small
		Suitable for grommets	1 x KT large

KEL 24|10-E


Part No.	49056	Height	17 mm
EAN	4251269312212	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	39	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	83 mm	Min. cable diam., with connector	10 x KT small
		Suitable for grommets	

KEL 24|10-E V2A


Part No.	49056.200	Height	17 mm
EAN	4251269312229	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	40	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	83 mm	Min. cable diam., with connector	10 x KT small
		Suitable for grommets	

KEL 24|9-E


Part No.	42207	Height	17 mm
EAN	4251269307973	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	30	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	83 mm	Min. cable diam., with connector	7 x KT small
		Suitable for grommets	2 x KT large

KEL 24|9-E V2A


Part No.	42207.200	Height	17 mm
EAN	4251269307980	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	30	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	83 mm	Min. cable diam., with connector	7 x KT small
		Suitable for grommets	2 x KT large

KEL 24|20-MT


Part No.	42232	Height	17 mm
EAN	4251269308215	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	80	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	20 x KT small
		Suitable for grommets	

KEL 24|20-MT V2A


Part No.	42232.200	Height	17 mm
EAN	4251269308222	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	80	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	102 mm	Min. cable diam., with connector	20 x KT small
		Suitable for grommets	

KEL 24|17-MT


Part No.	42224	Height	17 mm
EAN	4251269308130	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	65	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	16 x KT small
		Suitable for grommets	1 x KT large

KEL 24|17-MT V2A

Part No.	42224.200	Height	17 mm
EAN	4251269308147	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	65	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	102 mm	Min. cable diam., with connector	16 x KT small
		Suitable for grommets	1 x KT large

KEL 24|14-MT

Part No.	42225	Height	17 mm
EAN	4251269308154	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	50	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	12 x KT small
		Suitable for grommets	2 x KT large


KEL 24|14-MT V2A

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42225.200
4251269308161
1
48
35 mm
147 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
112 × 82 mm
6
5,8 mm
Stainless steel (V2A)
12 x KT small
2 x KT large


KEL 24|11-MT

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42222
4251269308093
1
35
35 mm
147 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
112 × 82 mm
6
5,8 mm
Mild steel, galvanically zinc plated
8 x KT small
3 x KT large


KEL 24|11-MT V2A

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42222.200
4251269308109
1
35
35 mm
147 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
112 × 82 mm
6
5,8 mm
Stainless steel (V2A)
8 x KT small
3 x KT large


KEL 24|8-MT

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42221
4251269308079
1
20
35 mm
147 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
112 × 82 mm
6
5,8 mm
Mild steel, galvanically zinc plated
4 x KT small
4 x KT large


KEL 24|8-MT V2A

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width


42221.200
4251269308086
1
20
35 mm
147 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets


17 mm
17 mm
112 × 82 mm
6
5,8 mm
Stainless steel (V2A)
4 x KT small
4 x KT large

KEL 24|30-2MT


Part No.	42234	Height	17 mm
EAN	4251269308253	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	120	No. of screw holes	8
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	30 x KT small
		Suitable for grommets	

KEL 24|30-2MT V2A


Part No.	42234.200	Height	17 mm
EAN	4251269308260	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	120	No. of screw holes	8
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	30 x KT small
		Suitable for grommets	

KEL 24|27-2MT


Part No.	42233	Height	17 mm
EAN	4251269308239	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	105	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	26 x KT small
		Suitable for grommets	1 x KT large

KEL 24|27-2MT V2A

Part No.	42233.200	Height	17 mm
EAN	4251269308246	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	105	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	26 x KT small
		Suitable for grommets	1 x KT large


KEL 24|24-2MT

Part No.	42227	Height	17 mm
EAN	4251269308192	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	90	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	22 x KT small
		Suitable for grommets	2 x KT large

KEL 24|24-2MT V2A


Part No. **42227.200**
 EAN **4251269308208**
 Package quantity **1**
 For max. no. of cables **90**
 Max. cable diameter **35 mm**
 Length **147 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **112 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector
 Suitable for grommets **22 x KT small**
2 x KT large

KEL 24|21-2MT


Part No. **42226**
 EAN **4251269308178**
 Package quantity **1**
 For max. no. of cables **75**
 Max. cable diameter **35 mm**
 Length **147 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **112 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector
 Suitable for grommets **18 x KT small**
3 x KT large

KEL 24|21-2MT V2A


Part No. **42226.200**
 EAN **4251269308185**
 Package quantity **1**
 For max. no. of cables **75**
 Max. cable diameter **35 mm**
 Length **147 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **112 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector
 Suitable for grommets **18 x KT small**
3 x KT large

KEL 24|12-2MT


Part No. **42223**
 EAN **4251269308116**
 Package quantity **1**
 For max. no. of cables **30**
 Max. cable diameter **35 mm**
 Length **147 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **112 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector
 Suitable for grommets **6 x KT small**
6 x KT large


KEL 24|12-2MT V2A

Part No. **42223.200**
 EAN **4251269308123**
 Package quantity **1**
 For max. no. of cables **30**
 Max. cable diameter **35 mm**
 Length **147 mm**
 Width **146 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **112 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector
 Suitable for grommets **6 x KT small**
6 x KT large

KEL 16|8


Part No.	42168	Height	17 mm
EAN	4251269307911	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	32	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	8 x KT small
		Suitable for grommets	

KEL 16|8 V2A


Part No.	42168.200	Height	17 mm
EAN	4251269307928	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	30	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	8 x KT small
		Suitable for grommets	

KEL 16|5


Part No.	42165	Height	17 mm
EAN	4251269307898	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	17	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	1 x KT large

KEL 16|5 V2A


Part No.	42165.200	Height	17 mm
EAN	4251269307904	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	17	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	1 x KT large

KEL 16|4


Part No.	42164	Height	17 mm
EAN	4251269307874	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	

KEL 16|4 V2A


Part No.	42164.200	Height	17 mm
EAN	4251269307881	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	4 x KT small

KEL 16|2


Part No.	42162	Height	17 mm
EAN	4251269307850	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	2	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT large

KEL 16|2 V2A


Part No.	42162.200	Height	17 mm
EAN	4251269307867	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	2	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT large

KEL 16|12-E


Part No.	42141	Height	17 mm
EAN	4251269307713	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	48	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	84 mm	Min. cable diam., with connector	
		Suitable for grommets	12 x KT small

KEL 16|12-E V2A


Part No.	42141.200	Height	17 mm
EAN	4251269307720	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	48	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	84 mm	Min. cable diam., with connector	
		Suitable for grommets	12 x KT small

KEL 16|6-E


Part No.	42140	Height	17 mm
EAN	4251269307690	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	18	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	84 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	2 x KT large

KEL 16|6-E V2A


Part No.	42140.200	Height	17 mm
EAN	4251269307706	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	18	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	84 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	2 x KT large

KEL 16|16-MT


Part No.	42145	Height	17 mm
EAN	4251269307775	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 82 mm
For max. no. of cables	64	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	16 x KT small
		Suitable for grommets	16 x KT small

KEL 16|16-MT V2A

Part No.	42145.200	Height	17 mm
EAN	4251269307782	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 82 mm
For max. no. of cables	61	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	102 mm	Min. cable diam., with connector	16 x KT small
		Suitable for grommets	16 x KT small

KEL 16|10-MT


Part No.	42144	Height	17 mm
EAN	4251269307751	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 82 mm
For max. no. of cables	34	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	8 x KT small
		Suitable for grommets	2 x KT large

KEL 16|10-MT V2A

Part No. **42144.200**
 EAN **4251269307768**
 Package quantity **1**
 For max. no. of cables **34**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **102 mm**

Part No. **42144.200**
 EAN **4251269307768**
 Package quantity **1**
 For max. no. of cables **34**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **102 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 82 mm**
 No. of screw holes **6**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector
 Suitable for grommets **8 x KT small**
2 x KT large

KEL 16|4-MT

Part No. **42143**
 EAN **4251269307737**
 Package quantity **1**
 For max. no. of cables **4**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **102 mm**

Part No. **42143**
 EAN **4251269307737**
 Package quantity **1**
 For max. no. of cables **4**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **102 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 82 mm**
 No. of screw holes **6**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector
 Suitable for grommets **4 x KT large**

KEL 16|4-MT V2A

Part No. **42143.200**
 EAN **4251269307744**
 Package quantity **1**
 For max. no. of cables **4**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **102 mm**

Part No. **42143.200**
 EAN **4251269307744**
 Package quantity **1**
 For max. no. of cables **4**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **102 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 82 mm**
 No. of screw holes **6**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector
 Suitable for grommets **4 x KT large**

KEL 16|24-2MT

Part No. **42149**
 EAN **4251269307836**
 Package quantity **1**
 For max. no. of cables **96**
 Max. cable diameter **17 mm**
 Length **120 mm**
 Width **146 mm**

Part No. **42149**
 EAN **4251269307836**
 Package quantity **1**
 For max. no. of cables **96**
 Max. cable diameter **17 mm**
 Length **120 mm**
 Width **146 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector
 Suitable for grommets **24 x KT small**

KEL 16|24-2MT V2A

Part No. **42149.200**
 EAN **4251269307843**
 Package quantity **1**
 For max. no. of cables **96**
 Max. cable diameter **17 mm**
 Length **120 mm**
 Width **146 mm**

Part No. **42149.200**
 EAN **4251269307843**
 Package quantity **1**
 For max. no. of cables **96**
 Max. cable diameter **17 mm**
 Length **120 mm**
 Width **146 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector
 Suitable for grommets **24 x KT small**

KEL 16|12-2MT

Part No. **42148**
 EAN **4251269307812**
 Package quantity **1**
 For max. no. of cables **36**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **146 mm**


Part No. **42148**
 EAN **4251269307812**
 Package quantity **1**
 For max. no. of cables **36**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector
 Suitable for grommets **8 x KT small**
4 x KT large

KEL 16|12-2MT V2A


Part No. **42148.200**
 EAN **4251269307829**
 Package quantity **1**
 For max. no. of cables **36**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector **8 x KT small**
 Suitable for grommets **2 x KT large**

KEL 16|6-2MT


Part No. **42147**
 EAN **4251269307799**
 Package quantity **1**
 For max. no. of cables **6**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector **6 x KT large**
 Suitable for grommets

KEL 16|6-2MT V2A


Part No. **42147.200**
 EAN **4251269307805**
 Package quantity **1**
 For max. no. of cables **6**
 Max. cable diameter **35 mm**
 Length **120 mm**
 Width **146 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **86 × 126 mm**
 No. of screw holes **8**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector **6 x KT large**
 Suitable for grommets

KEL 10|6


Part No. **42216**
 EAN **4251269308055**
 Package quantity **10**
 For max. no. of cables **24**
 Max. cable diameter **17 mm**
 Length **98 mm**
 Width **58 mm**

Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **65 × 36 mm**
 No. of screw holes **4**
 Diam. of screw holes **5,8 mm**
 Screw material **Mild steel, galvanically zinc plated**
 Min. cable diam., with connector **6 x KT small**
 Suitable for grommets


KEL 10|6 V2A

Part No. **42216.200**
 EAN **4251269308062**
 Package quantity **10**
 For max. no. of cables **24**
 Max. cable diameter **17 mm**
 Length **98 mm**
 Width **58 mm**


Height **17 mm**
 Mounting height **17 mm**
 Cut-out size **65 × 36 mm**
 No. of screw holes **4**
 Diam. of screw holes **5,8 mm**
 Screw material **Stainless steel (V2A)**
 Min. cable diam., with connector **6 x KT small**
 Suitable for grommets

KEL 10|3


Part No.	42212	Height	17 mm
EAN	4251269308031	Mounting height	17 mm
Package quantity	10	Cut-out size	65 × 36 mm
For max. no. of cables	9	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	98 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	2 x KT small
		Suitable for grommets	1 x KT large

KEL 10|3 V2A


Part No.	42212.200	Height	17 mm
EAN	4251269308048	Mounting height	17 mm
Package quantity	10	Cut-out size	65 × 36 mm
For max. no. of cables	9	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	98 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	2 x KT small
		Suitable for grommets	1 x KT large

KEL-B4


Part No.	42204	Height	17 mm
EAN	4251269307935	Mounting height	17 mm
Package quantity	10	Cut-out size	46 × 46 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	

KEL-B4 V2A

Part No.	42204.200	Height	17 mm
EAN	4251269307942	Mounting height	17 mm
Package quantity	10	Cut-out size	46 × 46 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	

KEL-B1

Part No.	42206	Height	17 mm
EAN	4251269307959	Mounting height	17 mm
Package quantity	10	Cut-out size	46 × 46 mm
For max. no. of cables	1	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	1 x KT large
		Suitable for grommets	

KEL-B1 V2A

Part No.	42206.200	Height	17 mm
EAN	4251269307966	Mounting height	17 mm
Package quantity	10	Cut-out size	46 x 46 mm
For max. no. of cables	1	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	1 x KT large
		Suitable for grommets	

icotek[®]
smart cable management