

KT-SC | Multi-range grommets

for cable diameters 4 - 28 mm / IP54



The KT-SC grommets accept a wide range of cable diameters. This is a great benefit when the exact cable diameter is not known in advance.

The single circular membrane can be peeled away to accommodate the specific diameter of the cable or hose. For this purpose, only a small hole between the rings needs to be pierced. Then the corresponding ring can be removed. The peeled-off area is always round, ensuring a secure seal around cable/hose.

The KT-SC cable grommet is based on the KT grommet and enables flexible routing and sealing (IP54) of electrical cables and pneumatic hoses with diameters from 4 - 28 mm.

The KT-SC cable grommets are not split and therefore only usable for cables without connectors.

IP54

RINA

HL3
EN 45545-2

E45
Ei30
EN 45545-3

ECOLAB
certified

UV
ISO 4892-2A

PNEUMATICS

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free

Advantages & Benefits

- Large clamping range
- Easy storage
- Circular membranes can be peeled off easily
- It is possible to install rigid cables at angles
- Ideal for wiring non pre-terminated cables locally

Product types & Sizes


KT-SC large



Part No.	41485
EAN	4251269321474
Package quantity	10
For max. no. of cables	1
Color	gray (similar RAL 7035)
Length	41,5 mm
Width	42 mm

Height	19 mm
Mounting height	2 mm
For cable type	Round cable
Clamping range	1 x 5 - 28 mm

KT-SC small



Part No.	41490
EAN	4251269331329
Package quantity	10
For max. no. of cables	1
Color	gray (similar RAL 7035)
Length	21 mm
Width	21 mm

Height	19 mm
Mounting height	2 mm
For cable type	Round cable
Clamping range	1 x 4 - 12 mm

